

PE Shrink Tunnel

ATPE-4060A / APT-6040PE I / APT-6040PE II / APT-8040PE II

PE Shrink tunnel is equipped with fully re-circulating air chamber and discharge end cooling fans. This machine is special designed for PE film packaging and is the best couple with PE Sleeve wrapping machine. Like other shrink tunnels, this also can be integrated with L-Sealer machines or overwrapping machines for wrapping improvement.



APSS-7522 + APT-6040PEII



ATPE-4060A
European Version



Teflon Mesh Conveyor



Stainless Steel Net Conveyor



APT-6040PE I



Standard Feature

1. Top Fans recycling system
2. Dead roller conveyor
3. Conveyor speed adjustable by frequency inverter
4. Digital temperature control
5. With cooling fan at the end of tunnel
6. Metal heating element, long durable and easy maintenance

Option

1. Stainless steel net conveyor
2. Sponge roller at tunnel end
3. Teflon mesh conveyor
4. Additional tunnel height



Compliance with CE & UL Standard

All major parts use foreign product.

Specification

Model No.	APT-6040PE I	APT-6040PE II	APT-8040PE II	APT-10040PE II	APT-12540PE II
Tunnel size	1200x600x400	1800X600X400	1800x800x400	1800x1000x400	1800x1250x400
Machine size	2200x970x1600	2800X970X1600	2800x1170x1600	2800x1370x1600	2800x1620x1600
Power	380V/3ph, 12kw	380V/3ph, 18kw	380V/3ph, 21kw	380V/3ph, 30kw	380V/3ph, 30kw
Conveyor speed (Max.)	15M/min	20M/min	20M/min	20M/min	20M/min
Packed machine size (LxWxH)	2160x1060x1870	2960x1090x1870	2960x1280x1920	3060x1500x2020	3060x1810x2020
Machine weight	420/600 kg	640/800 kg	850/1010 kg	1000/1160 kg	1200/1400 kg

Other size available on request

