High Speed Fully Automatic Side Seal Packing Machine

APSS-5022/7522/10022/4015E/7030E



APSS-5022



Applicable:

Software, food, cosmetics, printing, pharmaceutical, flooring, ceramics, beverage, metal, plastics and other industries large quantities of shrink wrap. Suitable for OPP, POF, PE, PVC and other shrink packaging materials.





APSS-7522 + APT-8040PEII

Feature

- 1. Constant heated sealing blades can perform continuously, which enables no limit of product length and high capacity of up to 60 bags per minute.
- 2. Auto photocell infeed system provides both horizontal and vertical choices to suit various product sizes.
- 3. Product changeovers can be easily realized by hand wheel adjustments, no elements need to be replaced.
- 4. Machine produces an enclosed pack with sealing on 3 sides.
- 5. Applicable for PE, POF and other center-folded shrink films, especially for POF shrink film packing.
- 6. Automatic Waste Strip wind up design.
- 7. Motor-driven infeed conveyor and free roller Outfeed conveyor are options for fully automatic application.



歐華包裝企業有限公司 Alpha-Pack Enterprise Ltd.

leading specialist of packaging machinery manufacturer Unit 1406 Vanta Industrial Center 21-23 Tai Li Pai Road, Kwai Chung, Hong Kong Tel: (852) 2416 1237 Fax: (852) 2264 6540



mm.alpha-pack.com.hk



High Speed Fully Automatic Side Seal Packing Machine APSS-5022/7522/10022/4015E/7030E

Options:

- 1. Kissing belt(suitable for small, irregular products)
- 2. Printing Film Photo sensor
- 3. 1.5M infeed conveyor
- 4. Automatic Product Pusher
- 5. 3 meters length lugs pushing conveyor

Specification

Model No.	APSS-5022	APSS-7522	APSS-10022
Power Supply	220V/1PH, 3000W	380V/3PH, 4000W	380V/3PH, 5000W
Air Supply	6 bar, 10L/min	6 bar, 10L/min	6 bar, 10L/min
Sealing bar width	500mm	750mm	1000mm
Max. pack height	220mm	220mm	220mm
Sealing jaw driven by	Servo motor	Servo motor	Servo motor
Max. conveyor speed	35m/min	35m/min	35m/min
Max. packing speed	70ppm	50ppm	40ppm
Center seal function	Yes	Yes	Yes
Machine size	2130x1697x1722mm	2404x2153x1722mm	2130x1697x1722mm
Packing size	2210x2020x1720mm	2660x2110x1720mm, 1660x960x1170mm	2210x2020x1720mm, 1600x960x1170mm
Machine weight	760/1000kg	820/1136kg, 90/120kg	760/1000kg, 152/200kg

Model No.	APSS-4015E	APSS-7030E
Power Supply	220V/PH, 2000W	220V/1PH, 2500W
Air Supply	6 bar, 30L/min	6 bar, 30L/min
Sealing bar width	400mm	700mm
Max. pack height	150mm	300mm
Sealing jaw driven by	Cylinder	Cylinder
Max. conveyor speed	35m/min	35m/min
Max. packing speed	50ppm	30ppm
Center seal function	Yes	Yes
Machine size	1582x1500x1722mm	2404x2050x1722mm
Packing size	1810x1610x1720mm	2480x2080x1720mm, 1460x600x620mm
Machine weight	630/770kg	800/1110kg, 90/120kg

^{*}Special size available on request

All major parts use foreign product.







Compliance with CE & UL Standard





