

Semi-Automatic Sealing and Shrink Machine

AP-1622MKA COMBO/AP-1519A COMBO



AP-1622MKA-COMBO



AP-1519A-COMBO



Application

This machine can be applied to electronics, plastics, software, food, cosmetics, printing, pharmacy, flooring, ceramics, beverage and hardware industries of large batch quantity of shrinking & sealing. Suitable for PVC, POF, PE, PP and other shrink packaging materials.

Feature

1. Anti-adhesive Teflon Coated Sealing Blade ensures neat and firm seal without smoke pollution. Overheat protect function extends the life span; hand clamping protect device avoids mistakenly damaging the product and also for the safety of the operator.
2. Shrink tunnel adopts advanced heater bank and adjustable High Speed Blower to realize re-circulating air, shorten the heating-up time and reduce the heat lost to ensure the best packing performance.
3. Quick film loading Design and advanced pin perforation device.
4. Selected electrical components from reliable international manufacturer.
5. Easy adjustment of conveyor time, height of sealing table and tunnel makes this machine suitable for packing products in various heights.

Technical Specification

Model No.		AP-1622MKA-COMBO	AP-1622MKB-COMBO	AP-1519A-COMBO
Max.Package Size	L	500	500	400
	W	400	400	300
	H	200	200	150
Capacity (Bag per Min.)		10-15	10-15	10
Machine Size (mm)		2575x800x1550	2575x800x1550	1900x700x1350
Voltage		380V/3ph or 220V/3ph	380V/3ph or 220V/3ph	220V/1ph
Max. Power		10kw	10kw	4.5kw
Sealing Bar		Pneumatic	Manual	Manual
Packed Machine Size (Lx Wx H)(mm)		2480X760X1860	2480x760x1860	1960x770x1670
Machine Weight (Kgs)		420/554 kg	420/554 kg	300/415 kg